

BEST AVAILABLE COPY

AUG 16 2006

Application No. 10/058,229

Docket No. 300200286-3 (1509-266)

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) An audio user-interfacing method in which services are represented by audio labels presented in an audio field through respective synthesized sound sources, the method comprising:

(a) storing, for each service to be represented, service access data and data associating the service with at least one said sound source and specifying at least one audio label;

(b) generating an audio field in which said sound sources are synthesized at respective rendering positions to sound their associated service-representing audio labels and thereby present the user with a choice of services;

(c) selecting a service by indicating the selected service through its audible representation, and

(d) modifying the audio-field layout of (i) the service-representing sound sources and/or (ii) what services are represented in the audio field.

2. (Previously presented) A method according to claim 1, wherein step (c) includes the selecting and modifying steps being performed by a user of the method rotating and/or displacing the audio field to bring the sound source of a target service so the sound source lies in a predetermined selection direction.

BEST AVAILABLE COPY

Application No. 10/058,229

Docket No. 300200286-3 (1509-266)

3. (Currently amended) A method according to claim 1, wherein step (c) includes moving an audio-cursor sound source in the audio field so the audio-cursor sound source is aligned it-with the sound source of a target service.
4. (Previously presented) A method according to claim 1, wherein step (c) includes the user speaking the audio label of a target service, and using a speech recogniser to match, where possible, this spoken label to the stored audio labels.
5. (Original) A method according to claim 1, wherein the selection of a service in step (c) results in the service-representing sound sources being replaced by an audio interface to the service.
6. (Original) A method according to claim 1, wherein the access data of a said service is the path name on a local machine of a service executable file.
7. (Original) A method according to claim 1, wherein the access data of a said service is the address of a service resource on a remote machine to be accessed over a communications connection.
8. (Original) A method according to claim 1, wherein said services comprise one or more of the following service types: application software; a communication service; an entertainment service; a database-based information

Application No. 10/058,229

Docket No. 300200286-3 (1509-266)

resource; a file information resource; a transactional service; an augmented-reality service.

9. (Original) A method according to claim 1, wherein the rendering positions of the sound sources are specified in the audio field with at least two degrees of freedom.

10. (Original) A method according to claim 1, wherein at least one said audio label is a verbal service name or descriptor.

11. (Original) A method according to claim 1, wherein at least one said audio label is an audio feed from the service concerned.

12. (Original) A method according to claim 1, wherein at least one said audio label is a distinctive sound or sound sequence.

13. (Original) A method according to claim 1, wherein at least one said audio label is user specified.

14. (Original) A method according to claim 1, wherein at least one said audio label is provided by the corresponding service.

Application No. 10/058,229

Docket No. 300200286-3 (1509-266)

15. (Original) A method according to claim 1, wherein at least one service has on-going activity and provides notification of significant service-related events, these notifications being passed to the user in audible form through a said sound source associated with the service.

16. (Currently amended) A method according to claim 1, wherein the rendering positions of said sound sources are specified relative to an audio-field reference, ~~the~~ modifying the layout of the service-representing sound sources through the modification of the rendering positions of individual sound sources.

17. (Previously presented) A method according to claim 1, including varying the rendering positions of said sound source by varying an offset between (a) an audio-field reference relative to which the sounds sources are positioned in the audio field, and (b) a presentation reference determined by a mounting configuration of audio output devices through which the sound sources are synthesised.

18. (Original) A method according to claim 17, wherein said offset is varied to stabilise the audio field relative to one of: a user's head; a user's body; a vehicle in which the user is travelling; the world; this stabilisation taking account of whether the audio output devices are world, vehicle, body or head mounted, and, as appropriate, rotation of the user's head or body, or turning of the vehicle.

Application No. 10/058,229

Docket No. 300200286-3 (1509-266)

19. (Original) A method according to claim 17, wherein said offset is varied in response to user input via an input device.

20. (Canceled)

21. (Currently amended) Apparatus for providing an audio user interface in which services are represented by audio labels presented in an audio field through respective synthesized sound sources, the apparatus comprising:

- a memory for storing, for each service to be represented, service access data and data associating the service with at least one said sound source and specifying at least one audio label;
- rendering means for generating, through audio output devices, an audio field in which said sound sources are synthesized at respective rendering positions to provide sounds for their associated service-representing audio labels and thereby present the user with a choice of services;
- selection means for selecting a represented service by indicating the represented service ~~it~~ through its audible representation; and
- user input means for enabling a user to modify the audio-field layout of the service-representing sound sources and/or what services are represented in the audio field.

22. (Original) Apparatus according to claim 21, wherein the selection means comprises means for rotating and/or displacing the audio field to bring the sound

Application No. 10/058,229

Docket No. 300200286-3 (1509-266)

source of a target service to lie in a predetermined selection direction, and means for inputting a select command to select a service whose sound source is aligned with said selection direction.

23. (Previously presented) Apparatus according to claim 21, wherein the selection means comprises means for moving an audio-cursor sound source in the audio field to align the audio-cursor sound source with the sound source of a target service, and means for inputting a select command to select a service with which the sound source is aligned.

24. (Original) Apparatus according to claim 21, wherein the selection means comprises speech input means for recognising an audio label spoken by the user and selecting the corresponding service.

25. (Previously presented) Apparatus according to claim 21, further comprising means arranged to be responsive to the selection of a service by the selection means to replace the audio field of service-representing sound sources with an audio interface to the selected service.

26. (Previously presented) Apparatus according to claim 21, wherein the access data of a said service includes the path name on a local machine of a service executable file.

Application No. 10/058,229

Docket No. 300200286-3 (1509-266)

27. (Previously presented) Apparatus according to claim 21, wherein the access data of a said service includes the address of a service resource on a remote machine to be accessed over a communications connection.

28. (Original) Apparatus according to claim 21, wherein said services comprise one or more of the following service types: application software; a communication service; an entertainment service; a database-based information resource; a file information resource; a transactional service; an augmented-reality service.

29. (Canceled)

30. (Previously presented) Apparatus according to claim 21, wherein at least one said audio label includes a verbal service name or descriptor.

31. (Previously presented) Apparatus according to claim 21, wherein at least one said audio label includes an audio feed from the service concerned.

32. (Previously presented) Apparatus according to claim 21, wherein at least one said audio label includes a distinctive sound or sound sequence.

33. (Original) A method according to claim 21, further comprising means for enabling a user to specify said audio labels.

Application No. 10/058,229

Docket No. 300200286-3 (1509-266)

34. (Original) A method according to claim 21, further comprising means for receiving audio-label specifying data from the corresponding service and storing it in said memory.

35. (Original) Apparatus according to claim 21, wherein at least one service has on-going activity and the apparatus further comprises means for receiving, from that service, notification of significant service-related events, and for causing these notifications to be output to the user in audible form through a said sound source associated with the service.

36. (Original) Apparatus according to claim 21, wherein the rendering positions of said sound sources are specified relative to an audio-field reference, the said user input means is operative to modify the layout of the service-representing sound sources through the modification of the rendering positions of individual sound sources.

37.-39. (Canceled)

40. (Original) Apparatus according to claim 21, further comprising means for enabling a user to modify which services are represented in the audio field.

Application No. 10/058,229

Docket No. 300200286-3 (1509-266)

41. (Previously presented) Apparatus for providing an audio user interface in which services are represented by audio labels presented in an audio field through respective synthesized sound sources, the apparatus comprising: a memory for storing, for each service to be represented, service access data and data associating the service with at least one said sound source and specifying at least one audio label; a rendering subsystem arranged to generate, through audio output devices, an audio field in which said sound sources are adapted to be synthesized at respective rendering positions to provide sounds for their associated service-representing audio labels; a selection arrangement operative to select a represented service by identifying it through at least one of its sound source and audio label; and user input functionality for enabling a user to modify the audio-field layout of the service-representing sound sources and/or what services are represented in the audio field.

42. (Original) Apparatus according to claim 41, wherein the selection arrangement comprises an arrangement for rotating and/or displacing the audio field to bring the sound source of a target service to lie in a predetermined selection direction, and an arrangement for inputting a select command to select a service whose sound source is aligned with said selection direction.

43. (Original) Apparatus according to claim 41, wherein the selection arrangement comprises an arrangement for moving an audio-cursor sound source in the audio field to align it with the sound source of a target service, and an arrangement

Application No. 10/058,229

Docket No. 300200286-3 (1509-266)

for inputting a select command to select a service with which the sound source is aligned.

44. (Original) Apparatus according to claim 41, wherein the selection means comprises a speech input subsystem operative to recognise an audio label spoken by the user and select the corresponding service.

45. (Original) Apparatus according to claim 41, further comprising functionality responsive to the selection of a service by the selection arrangement to replace the audio field of service-representing sound sources with an audio interface to the selected service.

46. (Previously presented) A method according to claim 1, wherein step (d) includes the user modifying which services are represented in the audio field.

47. (Previously presented) A method according to claim 1, wherein step (d) includes the user modifying the service representing sound sources.

48. (Currently amended) A method according to claim 47, wherein step (d) includes the user modifying the service representing sound sources.